



## 1 产品特性 Product Specialties

- 1.1 内部结构集成式 Internal structure integration type;
- 1.2 外部结构标准式 External structure standard type;
- 1.3 整定设置简单式 Adjusting set-up simplifying type;
- 1.4 功能模式多样式 Function mode diversification type.

## 2 产品型号及含义 Product Types and Meanings

XJ3 AC380V

—— 电源电压 Voltage  
—— 继电器型号 Relay Type

## 3 主要技术参数 Main Technological Parameter

电源电压 Voltage	AC380V/50Hz	
延时范围 Time Range	断相错相序(Open-phase wrong phase sequence) ≤ 2s	
安装形式 Contact Ratings	装置式 Installation type	
触点容量 Contact Capacity	AC220V: 5A DC24V: 7A	
环境温度 Operating Temperature	-10℃ ~ 50℃	
湿度 Humidity	35%~85%	
电寿命 Electricity Life	1 × 10 <sup>5</sup> 次	
对应型号 Parallelism Type	保护功能 Protection Function	延时范围 Time Range
XJ3	断相相序保护 Open-phase phase-sequence protection	≤ 2S
XJ4	断相相序保护 Open-phase phase-sequence protection	≤ 2S
XJ5	断相相序保护 Open-phase phase-sequence protection	≤ 2S
XJ6	断相相序保护 Open-phase phase-sequence protection	≤ 2S
APR-3	断相相序保护 Open-phase phase-sequence protection	≤ 2S
APR-4	断相相序保护 Open-phase phase-sequence protection	≤ 2S

## 4 外形安装尺寸、应用电路举例 Outline and mounting dimensions, Applied circuit instance

